



EXCETEK NP400L

Call for pricing

[1-815-597-5341](tel:1-815-597-5341)

Comply with TUV CE conformity, both safety and desired design with easy operation.

Power slider door design to save installation space and light operation.

High Precision - Smart Corner Control □ Stable Discharge Module □ SFC Super Finish Circuit.

Efficiency - DPM module □ Entrance mark control □ EF Electrolysis Free generator system.

Cost Saving - Intelligent Power Management □ Save Wire Consumption □ Low running cost.

Intelligent Networking - Remote monitor and management □ Connect all Controller □ Portable device monitor.

Automation - High speed Auto Wire Threading □ Workpiece Transfer Robot □ Auto Measurement and Correction.

STARTING AT \$95,500

SKU: N/A

Category: [New Machines](#)

ADDITIONAL INFORMATION

| | |
|----------------------------------|--|
| Max Work Piece Size | 29.53 x 21.65 x 8.46 in |
| Wire Diameter | 0.006 - 0.012 in |
| Max Work Piece Weight | 1,102 lbs |
| Number of Axes Controlled | XY axis linear motor, UV Z axis AC servo motor |
| Maximum Taper Angle | ±22°/ 3.15 in with wide diamond guide and nozzle |
| Travel (X/Y) | 15.75 x 11.81 in |
| U & V Axis Travel | 3.15 x 3.15 in |
| Z Axis Travel | 8.66 in |
| Machine Dimensions | 89 x 100 x 83 in |
| Machine Weight | 6724 lbs |
| Dielectric Tank Capacity | 172 g |
| Deionzer | Auto |
| Paper Filter | 2 / pcs |
| Chiller Unit | Auto |
| Power Needed | 220 v +5%, 3 Phase, 60 HZ |
| Dry Air Required | 100 psi |