



EXCETEK V1060

Call for pricing

[1-815-597-5341](tel:1-815-597-5341)

- Rigid U, V truss design
- Stainless steel work table with hardness HRC 50°.
- High response AC servo motor for guaranteed accuracy.
- Extra wide machine base.
- Water cooled lower arm prevents thermal expansion caused by heat buildup for improved accuracy.

SKU: N/A

Categories: [New Machines](#)

ADDITIONAL INFORMATION

Max Workpiece Size	59.06 x 39.37 x 13.58 in (Z350) / 59.06 x 39.37 x 19.49 in (Z500)
Travel of X/Y Axes	39.37 x 23.62 in
Travel of Z Axis	13.78 in x 19.69 in
Wire Diameter	.008~.013 in
Number of Axes	5 Axis AC Servo Motor
Machine Size	165.75 in x 128.35 x 90.94 in
Water Tank Capacity	Z350 / Z500 : 475 / 660 G
Max Workpiece Weight	6614 lbs
Travel of U/V Axes	6.30 x 6.30 in (Z350) / 10.24 x 10.24 in (Z500)
Max Taper Angle	±30°/ 3.94 in with wide diamond guide and nozzle
Machine Weight	16,095 lbs (Z350) / 16,865 lbs (Z500)
*Travel of Z Axis Option	19.69 in (Submerged height 19.69 in)
Power Needed	220 v +5%, 3 Phase, 60 HZ
Total Power Required	34.12 A (13 KVA)
Air Needed	100 psi