



EXCETEK V1060

Call for pricing or Make an offer

[1-815-597-5341](tel:1-815-597-5341)

- Rigid U, V truss design
- Stainless steel work table with hardness HRC 50°.
- High response AC servo motor for guaranteed accuracy.
- Extra wide machine base.
- Water cooled lower arm prevents thermal expansion caused by heat buildup for improved accuracy.

STARTING AT \$172,900

SKU: N/A

Category: [New Machines](#)

ADDITIONAL INFORMATION

| | |
|---------------------------------|---|
| Max Workpiece Size | 59.06 x 39.37 x 13.58 in (Z350) / 59.06 x 39.37 x 19.49 in (Z500) |
| Travel of X/Y Axes | 39.37 x 23.62 in |
| Travel of Z Axis | 13.78 in x 19.69 in |
| Wire Diameter | .008~.013 in |
| Number of Axes | 5 Axis AC Servo Motor |
| Machine Size | 165.75 in x 128.35 x 90.94 in |
| Water Tank Capacity | Z350 / Z500 : 475 / 660 G |
| Max Workpiece Weight | 6614 lbs |
| Travel of U/V Axes | 6.30 x 6.30 in (Z350) / 10.24 x 10.24 in (Z500) |
| Max Taper Angle | ±30°/ 3.94 in with wide diamond guide and nozzle |
| Machine Weight | 16,095 lbs (Z350) / 16,865 lbs (Z500) |
| *Travel of Z Axis Option | 19.69 in (Submerged height 19.69 in) |
| Power Needed | 220 v +5%, 3 Phase, 60 HZ |
| Total Power Required | 34.12 A (13 KVA) |
| Air Needed | 100 psi |