



FUJI CSD-300R TWIN SPINDLE LATHE

Call for pricing

[1-815-597-5341](tel:1-815-597-5341)

The CSD-300R Twin Spindle Lathe features live tools for the fastest part-to-part (takt time) in its class. These parallel twin spindle CNC lathes include both Z- and X-axis box way slides for heavy cutting, superior surface finish and longer tool life.

This series is equipped with Fuji-engineered hydraulic clamping gantry robot loaders to maintain tight tolerances.

- Reliable automated heavy parts loading
 - 200mm x 100mm
 - (7.87 x 3.93 inch) and 5kg + 5kg capacity
 - 8" - 10" workholding
- Quick and accurate automated turning and handling of complex parts reduces labor costs and increases productivity
- Turret capable of achieving speed of 0.26 sec/index.
 - Swivel control panel
 - Rear or optional side positioned discharge chip conveyor
- Maintenance items are all conveniently located in one section of the machine

SKU: N/A

Category: [New Machines](#)

ADDITIONAL INFORMATION

Recommended work size	200 x 100 mm (7.9 x 3.9 inch)
Spindle Diameter	100 mm (3.94 inch)
Spindle Nose	A2-6
Spindle Bore	56 mm (2.2 inch)
Spindle Speed - rpm	Max. 3630 (optional 4000)
Spindle Motor	11/15 kW (15/20 HP)
Slide stroke: X-axis	140 mm (5.5 inch)
Slide stroke: Z-axis (ram reverse)	200 mm (7.9 inch)
Total Tool Stations	10 + 10
Robot Controller	FANUC
LIVE TOOL - max. Clamping Tool Dia.	16 mm
LIVE TOOL - No. Stations	10 Position
LIVE TOOL - Spindle Speed	Max. 4000 rpm
LIVE TOOL - Spindle Motor	2.7 kW (3.7 HP)