



HURCO HTL12-40I (12" CHUCK)

\$113,995.00

Hurco Toolroom Lathe, HTL Series

These box way, gap bed lathes are user friendly and makes it easy to load/unload bulky parts.

The gap can be removed to accommodate even larger parts close to the headstock. The WinMax control that slides along a rail on the front of the machine allows for ease of use.

The solid box way bed construction on the HTL series makes it a perfect fit for a wide range of applications.

STARTING AT \$113,995

SKU: N/A

Category: [New Machines](#)

ADDITIONAL INFORMATION

X-axis Travel	13 in
Z-Axis Travel	42 in
Max Swing Over Bed	Ø 27"
Max Swing Over Gap	Ø 34.2"
Max Swing Over Cross Slide	Ø 16.1"
Gap Distance	12.75"
Max Turning Length	39.3in
X-axis Rapid Traverse	500 ipm
Z-axis Rapid Traverse	500 ipm
Spindle Nose	A2-11
Spindle Speed (RPM)	2000 rpm
Peak Spindle Motor Horsepower	24 HP
Spindle Motor Torque	1,050 Ft-lb @ 125 rpm
Spindle Chuck Size	12 in
Spindle Bore Diam.	Ø 3.22"
Number of Stations	8
Rotation	Bi-Directional
Max Boring Bar Capacity	Ø 1.5"

Turret Index Time (Adjacent)	.45 sec.
Turret Index Time (Furthest location)	1.6 sec.
Tool Shank Width	1.0" x 1.0"
Max. Operating Dimensions (W x D x H)	171" x 115" x 81"
Machine Weight (approx.)	8,820 lbs.
Voltage Required	230 +/-5% VAC / 60 Hz
Air Requirements	5 CFM @ 80-100 psi
Power Rating	30 KVA (78.73 amps)