



## HURCO TMX10MYI PERFORMANCE LATHE (10" CHUCK, TAILSTOCK)

Call for pricing

[1-815-597-5341](tel:1-815-597-5341)

The TMXMY/S mill turn lathes are true slant-bed lathes with all-digital drives and motors and absolute encoders on all linear axes. The addition of the Y-axis allows you to machine a pocket with straight walls and flat bottoms or perform off-center machining operations with just a click of a box.

---

**SKU:** N/A

**Categories:** [New Machines](#)

## ADDITIONAL INFORMATION

<b>Distance Between Centers</b>	33.6 in
<b>Swing Over Bed Diameter</b>	22 in
<b>Swing Over Cross Slide Diameter</b>	22 in
<b>X, Z W, Y Axis Travel</b>	8.76 x 26.38 x 29.1 x +/- 2.16 in
<b>Max. Turning Diameter</b>	12.4 in
<b>Max. Turning Length</b>	24.7 in
<b>Max. Bar Capacity</b>	3.07 in
<b>3.5k</b>	197.2 lb/ft @ 1000 rpm (267.4 Nm @ 1000 rpm)
<b>Spindle Power</b>	37.6 hp (27.8 kw)
<b>Spindle Nose</b>	A2-8
<b>Chuck Diameter</b>	10 in
<b>Tool Capacity</b>	12 Stations
<b>Tool Type</b>	BMT65 / DIN 1809
<b>Turret Index Time-Adjacent</b>	0.31 seconds
<b>Turret Index Time-Furthest</b>	0.78 seconds
<b>Rapid Traverse X,Z,W, Y Axis</b>	945 in/min, 1,181 in/min, 1,181 in/min, 472 in/min
<b>Live Tooling Spindle Power</b>	8.5 hp (6.4 kw)
<b>Machine Height</b>	101.5 in

<b>Required floor space</b>	209.9 x 121.5 in
<b>Machine Weight</b>	16,976 lb (7,700 kg)
<b>Voltage Required</b>	230 VAC / 60 Hz +/- 5%
<b>Power Rating</b>	42 KVA (110.2 amps)