



TAKUMI VC-0852

Call for pricing

[1-815-597-5341](tel:1-815-597-5341)

VC Series vertical machining centers are fast, three-axis linear guide machining centers designed for customers doing batch or production work

Fast Rapids + High Precision

- Rapids of 1,417 inches per minute
- Perfect combination of fast cutting and high stability
 - Designed and built for mold machining
- Pre-tensioned ballscrews minimize thermal growth and improve accuracy
 - Ergonomic table simplifies setup
- Swiveling control panel optimizes floor space utilization
- Robust, precision-machined castings
 - Hand-scraped contact areas
- 24-tool, CAT 40, swing-arm ATC standard
- Integrated washdown and chip management system
- Spindle chiller maximizes heat dissipation

SKU: N/A

Categories: [New Machines](#)

ADDITIONAL INFORMATION

Travel	33.9" x 20.47" x 24"
Table Size	39.4" x 20.47"
Table Max Load	1102
Spindle Speed	12,000 RPM
Motor Power	10.1/14.8 HP (7.5/11 kW)
Spindle Taper	CAT/BT 40
Magazine Capacity	24 tools
Rapids	1,417 x 1,417 x 944 in
Machine Weight	12,566 lbs
Operating Dimensions	195.15 x 147.36 x 122.01 in
Pneumatic Pressure	5 CFM @ 85-115 psi
Electrical Power Consumption	30 KVA